

**Utförande:** Naturanodiserad aluminium, natur, mörkgrå- eller bronslackerad. Bländskydd av prismatic akryl.

**LED info:** Systemeffekt 17W alt 20W. Armaturlumen 1400LM alt. 1937LM. Korrelerad färgtemperatur 3000K. Färgtolerans SDCM 3. Färgåtergivning RA 80.

**Montage:** Dikt tak.

**Anslutning:** Snabbkopplingsplint, D108 mm 3x4mm<sup>2</sup> . D400 mm 5x4mm<sup>2</sup>, överkopplingsbar.

**Design:** Per Sundstedt.

W	D/MM	KG	ART
LED 1400LM	400	3,3	7407-3-XX
LED 1400LM	400	3,3	7407-3-XXHFF
LED 1937LM	400	3,3	7429-3-XX
LED 1937LM	400	3,3	7429-3-XXHFF

**Med inbyggd närvarosensor/With built in motion detector**

LED/1400LM	400	3,3	7407-3-XXS
LED/1400LM	400	3,3	7407-3-XXHFFS
LED 1937LM	400	3,3	7429-3-XXS
LED 1937LM	400	3,3	7429-3-XXHFFS

**Med nödljus 1h/With emergency light 1h**

LED/1400LM	400	3,3	7407-3-XXE
LED/1400LM	400	3,3	7407-3-XXHFFE
LED 1937LM	400	3,3	7429-3-XXE
LED 1937LM	400	3,3	7429-3-XXHFFE

XX = Färg/Color -38 Aluminium, -97 Brons/Bronze, -98 Mörkgrå/Dark grey.

HFF = Dimmbar - DALI, DSI, SwitchDim.

HFF = Dimmable with DALI, DSI, SwitchDim

**Finish:** Anodized aluminium, natural, bronze or dark grey painted and white painted steel. Diffuser in prismatic acrylic.

**LED info:** System power: 17W or. 20W. Luminaire Luminous Flux: 1400LM or 1937LM. CCT 3000K. SDCM 3. CRI 80.


**Installation:** Ceiling-installation.

**Connection:** Terminal block. D108 mm 3x4mm<sup>2</sup> . D400 mm 5x4mm<sup>2</sup>, two entry holes.

**Design:** Per Sundstedt.



7407



7429

