



Utförande: Lackerad svart (RAL 9005), silvergrå (RAL 9006) alt.

galvaniserad metall. Härdat glas.

LED info: Armaturlumen se nedan. Symmetrisk alt asymmetrisk ljusbild.

Korrelerad färgtemperatur 3000K. Färgtolerans SDCM 3. Färgåtergivning RA >80.

Montage: Monteras på stolpe D60mm.

Anslutning: Kabel med snabbkoppling i stolpe.

Design: Jens Fager 2016.

W		FÄRG/COLOUR	ART.
LED 1940LM/32W	Asymm	Svart/Black	8294-1-06
LED 1940LM/32W	Asymm	Svart/Black	8294-1-06HFF
LED 1940LM/32W	Asymm	Svart/Black	8294-1-06N
LED 1940LM/32W	Asymm	Grå/Grey	8294-1-10
LED 1940LM/32W	Asymm	Grå/Grey	8294-1-10HFF
LED 1940LM/32W	Asymm	Grå/Grey	8294-1-10N
LED 1940LM/32W	Asymm	Galv/Galvanized	8294-1-83
LED 1940LM/32W	Asymm	Galv/Galvanized	8294-1-83HFF
LED 1940LM/32W	Asymm	Galv/Galvanized	8294-1-83N
LED 1920LM/32W	Symm	Svart/Black	8295-1-06
LED 1920LM/32W	Symm	Svart/Black	8295-1-06HFF
LED 1920LM/32W	Symm	Svart/Black	8295-1-06N
LED 1920LM/32W	Symm	Grå/Grey	8295-1-10
LED 1920LM/32W	Symm	Grå/Grey	8295-1-10HFF
LED 1920LM/32W	Symm	Grå/Grey	8295-1-10N
LED 1920LM/32W	Symm	Galv/Galvanized	8295-1-83
LED 1920LM/32W	Symm	Galv/Galvanized	8295-1-83HFF
LED 1920LM/32W	Symm	Galv/Galvanized	8295-1-83N

HFF = Dimmbar DALIDimmable DALI.

N = Nattsänkning/Night-time dimming

Finish: Painted black (RAL 9005), silvergrey (RAL9006) or galvanized metal.

Tempered glass. Symmetrical or asymmetrical light beam.


LED info: Led see above. CCT 3000K. SDCM 3. CRI >80

Installation: On pole top D60mm.

Connection: Cable with quick connection inside the pole.

Design: Jens Fager 2016.

8295-sym



8294-asym

