



Utförande: Kromad pendel och takkopp. Kupa av opalglas. D250-300 mm har stängd kupa D350-450 mm är öppen nedåt.

LED information: Systemeffekt W Armaturlumen 1500LM Korrelerad färgtemperatur 3000K. Färgtolerans SDCM 3. Färgåtergivning RA 80.

Montage: I takkrok, dikt tak.

Anslutning: Kopplingsplint 3x4mm². Överkopplingsbar.

W	D/MM	GLAS/GLASS	V/KG	ART
E27/max 70W	250	Opal	2,3	5270-2-20
E27/max 70W	300	Opal	2,5	5270-3-20
E27/max 70W	350	Opal	2,7	5270-4-20
E27/max 70W	400	Opal	2,9	5270-5-20
E27/max 70W	450	Opal	3,2	5270-6-20
LED/1500LM	350	Opal	2,7	5276-4-20
LED/1500LM	350	Opal	2,7	5276-4-20HFF
LED/1500LM	400	Opal	2,9	5276-5-20
LED/1500LM	400	Opal	2,9	5276-5-20HFF
LED/1500LM	450	Opal	3,2	5276-6-20
LED/1500LM	450	Opal	3,2	5276-6-20HFF

HFF = Dimmbar med DALI, DSI, SwitchDim

HFF = Dimmable with DALI, DSI, SwitchDim

Finish: Chromed pendant. Shade in opal glass.

D250-300 mm are closed D350-450 mm are open.

LED information: System power: W. Luminaire Luminous Flux: 1500LM CCT 3000K. SDCM 3. CRI 80.

Installation: Ceiling-hook.

Connection: Terminal block 3x4mm².

